

Produkt-Datenblatt

Technische Daten, Spezifikationen

Kontakt

**Technischer und kaufmännischer Vertrieb, Preis-
auskünfte, Angebote, Test-Geräte, Beratung vor Ort:**

Tel: (0 81 41) 52 71-0

FAX: (0 81 41) 52 71-129

Aus dem Ausland:

Tel: ++49 - 81 41 - 52 71-0

FAX: ++49 - 81 41 - 52 71-129

E-Mail: sales@meilhaus.com

Internet:

www.meilhaus.com

Web-Shop:

www.MEsstechnik24.de | www.MEasurement24.com

Web Kontakt-Formular:

www.meilhaus.de/infos/Kontakt.htm

Per Post:

Meilhaus Electronic GmbH

Am Sonnenlicht 2

D-82239 Alling bei München

MEsstechnik fängt mit ME an.

www.meilhaus.com

Erwähnte Firmen- und Produktnamen sind zum Teil
eingetragene Warenzeichen der jeweiligen Hersteller.
Preise in Euro zzgl. gesetzl. MwSt. Irrtum und Änderung
vorbehalten.

© Meilhaus Electronic bzw. Hersteller:
www.meilhaus.de/infos/impressum.htm


MEILHAUS
ELECTRONIC

Querx TH

Web Thermometer / Hygrometer and Data Logger



Querx TH is an Ethernet-based thermo-hygrometer with integrated data logger, alert functionality and numerous interfaces for manual and automated data access.

The stand-alone device is configured and operated via a graphical web interface.

Querx TH supports several cloud services. So you have access to measured data at anytime and from everywhere via web, app and API.

Models



Querx TH

Article EGN600214



Querx TH Set

Article EGN600114



Set: Querx TH plus Ethernet cable, micro-USB cable, USB power supply (GB, EU, US or AU), CD with documentation

Fields of Application

- Production and quality assurance
- Food hygiene (dry storages)
- Server room and rack monitoring
- Remote property monitoring
- Preventive conservation of cultural goods
- Climate monitoring in churches, wine cellars, paper warehouses
- and many more

Features

Integrated sensors

Temperature
Humidity
Dew point calculation

Network connection

100BaseT / RJ45 jack

Data logger

Configurable logging interval
Capacity: 73,728 records,
51 days (1 / min)
to 8.4 years (1 / h)

Web interface

Graphical web interface

Configuration

Automatic (Zeroconf, mDNS, DHCP)

Export data formats

CSV
XML

M2M protocols

HTTP (XML, CSV, JSON)
SNMPv1
Modbus/TCP
Syslog

Cloud exports

Xively
ThingSpeak

Types of alerts

Temperature / humidity:
too high, too low
rising too fast, dropping too fast
Dew point:
too high / too low

Alert notifications

E-mails (StartTLS / TLS)
SNMP traps
Syslog messages

Calibration

Optional accredited calibration

Temperature units

°Celsius
°Fahrenheit
Kelvin

Languages

Documentation:
German, English
Software:
German, English

Specifications

Technical data	
Measuring range temperature	-40 °C to 85 °C (-40 °F to 185 °F)
Accuracy temperature	±0.4 °C from -10 °C to 85 °C ±1.0 °C from -40 °C to -10 °C (±0.7 °F from 14 °F to 185 °F ±1.8 °F from -40 °F to 14 °F)
Resolution temperature	0.1 °C (0.2 °F)
Long-term stability temperature	0.01 °C (0.018 °F) per year, typical
Sampling rate	1 second
Measuring range humidity	0 % to 95 % RH
Accuracy humidity	±2 % RH from 0 % to 80 % RH and 30 °C (86 °F) ±4.0 % RH from 80 % to 95 % RH and 30 °C (86 °F)
Resolution humidity	1 % RH
Long-term stability humidity	0.25 % per year, typical
Humidity sensor	CMOS IC with polyimide film
Calibration	Optional accredited calibration
Ethernet	10/100 Mbit RJ45, HP Auto-MDIX, static or dynamic IP (DHCP client)
System	Nut/OS 5
Firmware updates	Via web interface, rescue function
Logging interval	Configurable
Data capacity	73,728 records, 51 days (1 / min) to 8.4 years (1 / h)
M2M	HTTP (XML, CSV, JSON), Syslog, Modbus/TCP, SNMP
Web interface	Interactive chart, live update, HTML5, CSS3, XML and CSV
Security	Start/TLS, password protection, user management (3 users / 3 groups)

E-mail	Up to 4 recipients via 2 SMTP servers
SNMP	SNMPv1 agent and traps
Status LED	3 colours: red, green, yellow
Date / time	Battery backed real-time clock, SNTP update
Power supply	5 VDC to 5.5 VDC over micro-USB
Consumption	Typical 120 mA 0.6 W, max. 200 mA 1 W
Environment	
Operating conditions	-40 °C to 85 °C, max. 95 % RH (-40 °F to 185 °F, max. 95 % RH)
Storage conditions	-40 °C to 85 °C, max. 95 % RH (-40 °F to 185 °F, max. 95 % RH)
Mechanical data	
Housing material	ABS thermoplastic, black, RAL 9011
Housing dimensions	56.3 x 40 x 21 mm (2.2 x 1.6 x 0.8 in) plus sensing cable
Length sensing cable	340 mm (13.4 in)
Weight	35 g (0.07 lb)
Connector	RJ45 (Ethernet), micro-USB
Mounting	Wall mounting
Certificates	
Interference immunity	EN 61326-1:2013 class A EN 61000-4-2:2009 EN 61000-4-3:2011 EN 61000-4-4:2013 EN 61000-4-6:2009 EN 61000-4-8:2010
Emitted interference	EN 61326-1:2013 class B EN 55011:2011
Flammability class	UL94V-0
Protection mark	IP20
RoHS compliance	EU directive 2011/65/EU
Conformity	CE conform